

## 1M SC/SC Mode Conditioning Fiber Patchcord



Part No. FB-MCF-CC

Rating: Not Rated Yet

[Ask a question about this product](#)

Manufacturer [Cables and Chips Inc](#)

Description DESCRIPTION	62.5?M MMF	50?M MMF
Operating wavelength	1310nm	
Maximum insertion loss	0.5dB	
Coupled power ratio (CPR)	28 to 40dB	12 to 20dB
Back reflection S/M channel	30dB	
Back reflection M/M channel	20dB	
Connector finish	PC or APC	
Ferrule radius of curvature	10 to 25mm	
Fibre height	-50 to 50nm	
Maximum angular offset	1°	
Sheath colour	Orange (yellow for SM leg)	Orange (yellow for SM leg)
DESCRIPTION		
Temperature Cycling	(IEC 61300-2-22) -40 to +75°C, 40 cycles =0.2dB Change	
Damp Heat	(IEC 61300-2-19) 60°C at 95% RH, 96 hours =0.2dB Change	
Vibration (Mated Pair)	(IEC 61300-2-1) 10-55 Hz, 1.5mm P to P =0.3dB Change	
Mating Durability	(IEC 61300-2-2) 1000 mating cycles Clean every 25	
Operating Temperature	< 0.2 dB Change (IEC 61300-2-22) -20°C to +60°C	

### Patch cord Specification

#### SPECIFICATION

Connectors available  
Product Packaging

Length

Types: FC, ST, SC, LC

Each patchcord is packaged individually and individually identified for traceability, test certification is supplied for each assembly.

2000mm ± 10mm

Other lengths available to order