

7M LC/LC MM DPX 62.5/125UM Fiber Patch Cord



FB-LL-MD6-07

Rating: Not Rated Yet
24 h

[Ask a question about this product](#)

Manufacturer [Cables and Chips Inc](#)

Description

Connector Specification

| | | |
|----------------------------|-----------|----------------|
| OPTICAL PERFORMANCE | MULTIMODE | CONFORMANCE |
| IL Max/Master (Acceptance) | 0.30dB | IEC 61300-3-4 |
| Ave/Master | 0.15dB | IEC 61300-3-4 |
| Ave/Random | 0.20dB | IEC 61300-3-34 |

Cable Specification

| | | |
|----------------------------|-------------------------|-------------------------|
| CHARACTERISTICS | SIMPLEX | DUPLEX |
| Cable Material | PVC, OFNR, OFNP or LSZH | PVC, OFNR, OFNP or LSZH |
| Strength Member | Aramid | Aramid |
| Crush (N) | 1000 | 1000 |
| Operating Temperature (?C) | -20 to 60 | -20 to 60 |
| Fire Specification | IEC 60332-1 | IEC 60332-1 |

Fiber Specification

| | |
|--------------------------|----------------------------|
| CHARACTERISTICS | |
| Attenuation (dB) / km | 2.8 @ 850nm / 0.8 @ 1300nm |
| Bandwidth OFL (MHz x km) | 220 @ 850nm / 600 @ 1300nm |