

12M SC/SC MM DPX 10GB 50/125um Fiber Patchcord



FB-CC-MDO3-12

Rating: Not Rated Yet  
24 h  
★★★★★

[Ask a question about this product](#)

Manufacturer [Cables and Chips Inc](#)

Description

Connector Specification

|                            |           |                |
|----------------------------|-----------|----------------|
| OPTICAL PERFORMANCE        | MULTIMODE | CONFORMANCE    |
| IL Max/Master (Acceptance) | 0.30dB    | IEC 61300-3-4  |
| Ave/Master                 | 0.15dB    | IEC 61300-3-4  |
| Ave/Random                 | 0.20dB    | IEC 61300-3-34 |

Cable Specification

|                            |                         |
|----------------------------|-------------------------|
| CHARACTERISTICS            |                         |
| Cable Material             | PVC, OFNR, OFNP or LSZH |
| Strength Member            | Aramid                  |
| Crush (N)                  | 1000                    |
| Operating Temperature (?C) | -20 to 60               |
| Fire Specification         | IEC 60332-1             |

Fiber Specification

|                           |                             |
|---------------------------|-----------------------------|
| CHARACTERISTICS           |                             |
| Attenuation (dB) / km     | 2.8 @ 850nm / 0.8 @ 1310nm  |
| Bandwidth OFL (MHz x km)  | 1500 @ 850nm / 500 @ 1310nm |
| Bandwidth LEMB (MHz X km) | 2000 @ 850nm                |