

## ST to SC Singlemode Duplex 9/125um Fiber Patchcord



From 1meter to 50meter

Rating: Not Rated Yet  
3-5 Days  
★★★★★

[Ask a question about this product](#)

Manufacturer [Cables and Chips Inc](#)

Description

### Connector Specification

OPTICAL PERFORMANCE	SINGLEMODE	CONFORMANCE
IL Max/Master (Acceptance)	0.30dB	IEC 61300-3-4
Ave/Master	0.18dB	IEC 61300-3-4
Ave/Random	0.18dB	IEC 61300-3-34
Return Loss	50/60dB	IEC 61300-3-6

### Cable Specification

CHARACTERISTICS	SIMPLEX	DUPLEX
Cable Material	PVC, OFNR, OFNP or LSZH	PVC, OFNR, OFNP or LSZH
Strength Member	Aramid	Aramid
Crush (N)	1000	1000
Operating Temperature (?C)	-20 to 60	-20 to 60
Fire Specification	IEC 60332-1	IEC 60332-1

### Fiber Specification

CHARACTERISTICS	
Attenuation (dB) / km	0.38 @ 1310nm / 0.25 @ 1550nm
Chromatic Dispersion (ps/nm x km)	3.0 @ 1310nm / 18.0 @ 1550nm